CARRIER SERIES





AUTOMOTIVE DESIGNED DASHBOARD, COLOR MATCHED CUP HOLDER INSERT



STEERING WHEEL



COLOR MATCHED DASHBOARD WITH FOUR CUP HOLDERS/CELL PHONE HOLDER




REAR-FACING, FLIP-FLOP SEAT KITS WITH STORAGE COMPARTMENT



14" ALLOY WHEEL RIMS WITH COLOR MATCHING INSERTS AND RADIAL DOT TIRES







CARRIER 6



CARRIER 8





SPECIFICATIONS

FORETSTER 6

DIMENSIONS

EXTERNAL DIMENSION	3760×1400×2200mm
WHEELBASE	2470mm
FRONT WHEEL TREAD	1000mm
REAR WHEEL TREAD	1025mm
BRAKING DISTANCE	≤4m
MIN TURNING RADIUS	4.4m
CURB WEIGHT	515kgs
MAX TOTAL MASS	1015kgs
FRAME	E-coat and powder coated chassis
BODY	TPO injection moulding front cowl and rear body

GENERAL

TIRE SIZE	14X7"Aluminum Wheel/ 23X10-14 Silent Tire with Off- road Thread
SEATING CAPACITY	Six persons
TOUCHSCREEN	No Touchscreen
AVAILABLE MODEL COLORS	Candy Apple Red, White, Black, Navy Blue, Silver, Green. PPG- Flamenco Red, Black Sapphire, Mediterranean Blue, Mineral White, Portimao Blue, Arctic Gray
AVAILABLE SEAT COLORS	Black&Black,Silvery&Black,Apple Red&Black

SPECIFICATION

SYSTEM VOLTAGE	48V
MOTOR POWER	6.3kw With EM Brake
CHARGING TIME	4-5h
CONTROLLER	400A
MAX SPEED	20-40m/h
MAX GRADIENT (FULL LOAD)	30%
BATTERY	48V Lithium battery

CARRIER 4

DIMENSIONS

EXTERNAL DIMENSION	3180×1400×1930mm
WHEELBASE	2450mm
FRONT WHEEL TREAD	880mm
REAR WHEEL TREAD	980mm
BRAKING DISTANCE	≤4m
MIN TURNING RADIUS	4.3m
CURB WEIGHT	434kgs
MAX TOTAL MASS	784kgs
FRAME	E-coat and powder coated chassis
BODY	TPO injection moulding front cowl and rear body

GENERAL

TIRE SIZE	14X7"Aluminum Wheel/ 215/35R14" Radial Tire
SEATING CAPACITY	Four persons
TOUCHSCREEN	No Touchscreen
AVAILABLE MODEL COLORS	Candy Apple Red, White, Black, Navy Blue, Silver, Green. PPG> Flamenco Red, Black Sapphire, Mediterranean Blue, Mineral White, Portimao Blue, Arctic Gray
AVAILABLE SEAT COLORS	Black&Black,Silvery&Black,Apple Red&Black

SPECIFICATION

SYSTEM VOLTAGE	48V
MOTOR POWER	6.3kw
CHARGING TIME	4-5h
CONTROLLER	400A
MAX SPEED	20-40km/h
MAX GRADIENT (FULL LOAD)	30%
BATTERY	48V Lithium battery

CARRIER 6

DIMENSIONS

EXTERNAL DIMENSION	3660×1400×1930mm
WHEELBASE	2450mm
FRONT WHEEL TREAD	880mm
REAR WHEEL TREAD	980mm
BRAKING DISTANCE	≤4m
MIN TURNING RADIUS	4.3m
CURB WEIGHT	469kgs
MAX TOTAL MASS	969kgs
FRAME	E-coat and powder coated chassis
BODY	TPO injection moulding front cowl and rear body

GENERAL

TIRE SIZE	14X7"Aluminum Wheel/ 215/35R14" Radial Tire
SEATING CAPACITY	Six persons
TOUCHSCREEN	No Touchscreen
AVAILABLE MODEL COLORS	Candy Apple Red, White, Black, Navy Blue, Silver, Green. PPG> Flamenco Red, Black Sapphire, Mediterranean Blue, Mineral White, Portimao Blue, Arctic Gray
AVAILABLE SEAT COLORS	Black&Black,Silvery&Black,Apple Red&Black

SPECIFICATION

SYSTEM VOLTAGE	48V
MOTOR POWER	6.3kw With EM Brake
CHARGING TIME	4-5h
CONTROLLER	400A
MAX SPEED	20-40km/h
MAX GRADIENT (FULL LOAD)	30%
BATTERY	48V Lithium battery

CARRIER 8

DIMENSIONS

_		
	EXTERNAL DIMENSION	4460×1400×1930mm
	WHEELBASE	3250mm
	FRONT WHEEL TREAD	880mm
	REAR WHEEL TREAD	980mm
	BRAKING DISTANCE	≤4m
	MIN TURNING RADIUS	4.8m
	CURB WEIGHT	544kgs
	MAX TOTAL MASS	1194kgs
	FRAME	Hot-galvanized chassis
	BODY	TPO injection moulding front cowl and rear body

GENERAL

TIRE SIZE	14X7"Aluminum Wheel/ 215/35R14" Radial Tire
SEATING CAPACITY	Eight persons
TOUCHSCREEN	No Touchscreen
AVAILABLE MODEL COLORS	Candy Apple Red, White, Black, Navy Blue, Silver, Green. PPG- Flamenco Red, Black Sapphire, Mediterranean Blue, Mineral White, Portimao Blue, Arctic Gray
AVAILABLE SEAT COLORS	Black&Black,Silvery&Black,Apple Red&Black

SPECIFICATION

SYSTEM VOLTAGE	48V
MOTOR POWER	6.3kw With EM Brake
CHARGING TIME	4-5h
CONTROLLER	400A
MAX SPEED	20-40km/h
MAX GRADIENT (FULL LOAD)	30%
BATTERY	48V Lithium battery











FORESTER 6 CARRIER 4

CARRIER 6

CARRIER 8



Self discharge max 3.2% per month Continuous charge current 540A ≤70A ≤145A Continuous discharge current Maximum discharge current 3C(30s) Quick charging time 1-2h Standard charging time 4-5h

	L4860	L48110	L48205
Charge temperature range	32°F to 110°F (0°C to 45°C)		
Discharge temperature range	-4°F to 140°F (-20°C to 55°C)		
Storage temperature range	-4°F to 113°F (1month)(-20°C to 45°C)		
Cell combination	16 in series circuit	16 in series circuit	16 in series circuit
Cell assembly	3.2V60Ah	3,2V110Ah	3.2V205Ah
Casing material	Aluminum Alloy	Aluminum Alloy	Stool with Flust-resistant Conting
Weight	56.8lbs(25.8kg)	102.7/bs(46.6kg)	173.3lbs(78.6kg)
Dimension(L*W*H)	13.5*12.8*9.4in	21.0*13.8*9.8in	27.1°13.7°8.9in
IP rate	iP66		

L series products are lithium-ion battery packs with integrated golf cart battery system. They are designed to replace the lead-acid batteries, which are available for drop-in replacement in golf carts easily. The benefits of lithium-ion battery include lighter weight, shorter charging time, longer life, free maintenance and to save much electricity bill for you. Our battery has an integrated management system which includes an On/Off switch and a state-of-charge(SOC) gauge.



All LED LIGHTING.











Beam At The Darkness! Eco-Friendly .Cost-efficient.Long Lasting.Hassle-free.

